

InSource Condensing Units - UL Recognized  
 115V-60Hz, R-134A, M/HBP

File # SA44169

						BTU/h Capacity @ Evaporator Temp		
Appl	Base P/N	Primary Source Compressor	Compressor Model	Fan Watts	Fan Blade - Dia / Pitch	0F Evap T	10F Evap	20F Evap T
						90F Ambient	90F Ambient	90F Ambient
M/HBP	CUA0020	Cubigel (Huayi)	GL80TE	6	8", 30 deg, CW	<b>1397</b>	<b>1742</b>	<b>2105</b>
M/HBP	CUA0025	Cubigel (Huayi)	GL90TE	6	8", 30 deg, CW	<b>1577</b>	<b>1968</b>	<b>2372</b>
M/HBP	CUA0033	Cubigel (Huayi)	GP12TE	9	8", 30 deg, CW	<b>2203</b>	<b>2750</b>	<b>3314</b>
M/HBP	CUA0038	Cubigel (Huayi)	GP14TE	16	10", 30 deg, CW	<b>2860</b>	<b>3558</b>	<b>4368</b>
M/HBP	CUA0050	Cubigel (Huayi)	GPY16RDa	16	10", 30 deg, CW	<b>3229</b>	<b>4006</b>	<b>4903</b>